

PRODUCT INFORMATION SHEET

Glue Gun Sticks



Characteristics

- transparent colour for versatile applications;
- made with the highest Class A quality materials: EVA, resin, paraffin;
- pre-heating time range 10-20 seconds;
- softening point temp. 80 °C;
- working temperature 100-200 °C;
- melt viscosity 15 PC (1.5 Pa*s);
- diameter: 11.2 mm;
- packaging 1 kg;
- possible applications: wood, plastic, ceramics, paperboard, glass.

Technical specifications

HT2C131	5902801214509	∅ 11.2 mm \longleftrightarrow 200 mm



**Höfert Technik GmbH, Pariser Platz 6a,
10117 Berlin, Deutschland**

Producent/ Manufacturer/ Hersteller/

Произведено для:

PL GTV Poland sp. z o.o. sp.k., ul. Przejazdowa 21
05-800 Pruszków, Polska/ Poland/ Polen/ Польша

Importer/ Импортёр:

Организация уполномоченная принимать претензии по качеству товара:

RU ООО «ГТВ РУС» 140073 Московская область, Люберецкий район, Поселок Томилино Микрорайон «Птицефабрика», Лит. 7А; info@hoegert.ru

HR GTV Croatia d.o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska

Distributor:

ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón 308, 46021 Valencia, Spain

CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince 879, 720 00 Ostrava Hrabová

BR GTV Brasil Comércio, Importação e Exportação EIRELI Rua William Booth 500 - Boqueirão Curitiba - Paraná, CEP: 81650-120, Brasil