

Worklight 550 lm



Product description

Double-sided, portable work lighting, which is characterised by very good quality of emitted light and high resistance to damage and durability. It is suitable for work in the most difficult conditions - construction, finishing, renovation, workshops and outdoors. It has strong and energy-saving LEDs with different lighting characteristics. SMD LEDs shine in a more diffuse way, so they may give impression as if they shine from different sources without glare. COB LEDs have more focused light, clearly emitted in a narrow beam from one point. It has 3 lighting modes: 550 lm for COB light and 350 lm and 120 lm for SMD light. Moreover, it has the function of smooth regulation of lighting intensity. Holding the button dims the light, stopped when the button is released. The lamp is powered by an efficient battery, ensuring continuous operation for up to 17 hours. The housing made of ABS with a high impact protection rating - IK07 guarantees full resistance to impact energy of 2 J, which is equivalent to an impact of a 500 g object from a height of 40 cm. Additionally, the housing is resistant to splashing water in IPX4 rating, which allows it to be safely used in light rain. It can work in a wide range of temperatures, outdoors in winter and in hot weather ranging from -20°C to +40°C. The handle working with a 360° tilt range allows the light to be directed in any direction. A strong magnet and a foldable hook for hanging make it possible to mount the floodlight anywhere and to free up hands for work. A socket with a 1/4" thread allows the floodlight to be mounted on a tripod. The charging indicator makes it possible to check the remaining battery power.

Characteristics

Max. luminous flux - 1,500 lm;

Three operating modes/operating time/beam length:

1. COB LEDs - 550 lm/ 4.5 H/ 170 m;
2. SMD LEDs 350 lm/ 5 H/ ? m;
3. SMD LEDs 120 lm/ 9 H/ 10 m;

Additional function - dimming;

Impact protection class - IK07 (equivalent to an impact of a 500 g object from a height of 40 cm);

Waterproof class - IPX4 - protection against splashing water

Power supply - polymer battery 3.7 V, 2000 mAh;

Max. working time - 9 H;

Max. charging time - 3.5 H;

Head tilt adjustment - 360°;

Mounting - magnets, hook for hanging , 1/4" socket;

Material - ABS;

Charging port - USB-C.

Technical data



11.2024

■ www.hoegert.com